



# SAFETY DATA SHEET

## 1. Identification

**Product identifier:** BASEBOARD WAX STRIPPER

Canadian Importer  
Advantage Maintenance Products Ltd.  
105 Scott Ave  
Paris, ON N3L 3E7  
(519) 442-7881

**Other means of identification**

**SDS number:** RE1000010712

**Recommended restrictions**

**Product use:** Cleaner

**Restrictions on use:** Not known.

### Manufacturer/Importer/Distributor Information

**Manufacturer**

Company Name: CLAIRES MANUFACTURING COMPANY  
Address: 1000 Integram Dr  
Pacific, MO 63069  
Telephone: 1-630-543-7600

**Emergency telephone number:** 1-866-836-8855

## 2. Hazard(s) identification

**Hazard Classification**

**Physical Hazards**

Flammable aerosol Category 1

**Health Hazards**

Skin Corrosion/Irritation Category 2

Serious Eye Damage/Eye Irritation Category 2A

Skin sensitizer Category 1

### Label Elements

**Hazard Symbol:**



**Signal Word:** Danger

**Hazard Statement:** Extremely flammable aerosol.  
Causes skin irritation.  
Causes serious eye irritation.  
May cause an allergic skin reaction.



### Precautionary Statements

- Prevention:** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/eye protection/face protection.
- Response:** IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see on this label). Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- Storage:** Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.
- Disposal:** Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

**Other hazards which do not result in GHS classification:** None.

### 3. Composition/information on ingredients

#### Mixtures

Chemical Identity	Common name and synonyms	CAS number	Content in percent (%)*
Ethanol, 2-butoxy-		111-76-2	10 - 30%
Butane		106-97-8	3 - 7%
Propane		74-98-6	1 - 5%
Oils, pine		8002-09-3	0.1 - 1%
Sodium hydroxide (Na(OH))		1310-73-2	0.1 - 1%
Ammonium hydroxide ((NH4)(OH))		1336-21-6	0 - 0.1%

\* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

### 4. First-aid measures

- Ingestion:** Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.
- Inhalation:** Move to fresh air.
- Skin Contact:** Get medical attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
- Eye contact:** Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.

#### Most important symptoms/effects, acute and delayed

**Symptoms:** No data available.

**Hazards:** No data available.



**Indication of immediate medical attention and special treatment needed**

**Treatment:** No data available.

**5. Fire-fighting measures**

**General Fire Hazards:** Use water spray to keep fire-exposed containers cool. Fight fire from a protected location. Move containers from fire area if you can do so without risk.

**Suitable (and unsuitable) extinguishing media**

**Suitable extinguishing media:** Use fire-extinguishing media appropriate for surrounding materials. Use fire-extinguishing media appropriate for surrounding materials.

**Unsuitable extinguishing media:** Do not use water jet as an extinguisher, as this will spread the fire. Do not use water jet as an extinguisher, as this will spread the fire.

**Specific hazards arising from the chemical:** Vapors may travel considerable distance to a source of ignition and flash back.

**Special protective equipment and precautions for firefighters**

**Special fire fighting procedures:** No data available.

**Special protective equipment for fire-fighters:** Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

**6. Accidental release measures**

**Personal precautions, protective equipment and emergency procedures:** Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

**Methods and material for containment and cleaning up:** Absorb spill with vermiculite or other inert material, then place in a container for chemical waste. Absorb spill with vermiculite or other inert material, then place in a container for chemical waste. Dike far ahead of larger spill for later recovery and disposal.

**Notification Procedures:** Prevent entry into waterways, sewer, basements or confined areas. Stop the flow of material, if this is without risk. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do so without risk. Dike for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Stop the flow of material, if this is without risk. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do so without risk.

**Environmental Precautions:** Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.



## 7. Handling and storage

**Precautions for safe handling:** Avoid contact with eyes. Wash hands thoroughly after handling. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source.  
Pressurized container: Do not pierce or burn, even after use. Avoid contact with skin. Avoid contact with eyes, skin, and clothing.

**Conditions for safe storage, including any incompatibilities:** Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.  
Aerosol Level 1 Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

## 8. Exposure controls/personal protection

### Control Parameters

#### Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Ethanol, 2-butoxy-	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Ethanol, 2-butoxy-	TWA	20 ppm 97 mg/m <sup>3</sup>	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (10 2006)
Ethanol, 2-butoxy-	15 MIN ACL	30 ppm	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Ethanol, 2-butoxy-	TWA	20 ppm	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2011)
Ethanol, 2-butoxy-	TWA	20 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
	8 HR ACL	20 ppm	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Ethanol, 2-butoxy-	TWA	20 ppm 97 mg/m <sup>3</sup>	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Ethanol, 2-butoxy-	TWA	20 ppm	US. ACGIH Threshold Limit Values, as amended (2008)
Butane	STEL	1,000 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (08 2017)
Butane	STEL	750 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2017)
	TWA	600 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2017)
Butane	TWA	800 ppm 1,900 mg/m <sup>3</sup>	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (12 2008)
Butane	TWA	1,000 ppm	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
Butane	8 HR ACL	1,000 ppm	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Butane	STEL	1,000 ppm	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2018)
	15 MIN ACL	1,250 ppm	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Butane	STEL	1,000 ppm	US. ACGIH Threshold Limit Values, as amended (03 2018)
Propane	TWA	1,000 ppm	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
Propane	8 HR ACL	1,000 ppm	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)



Propane	TWA	1,000 ppm 1,800 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (12 2008)
Propane	TWA	1,000 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	15 MIN ACL	1,250 ppm	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Sodium hydroxide (Na(OH))	CEILIN G	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Sodium hydroxide (Na(OH))	CEILIN G	2 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (10 2006)
Sodium hydroxide (Na(OH))	CEV	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (12 2007)
Sodium hydroxide (Na(OH))	Ceiling	2 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Sodium hydroxide (Na(OH))	CEILIN G	2 mg/m3	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2011)
Sodium hydroxide (Na(OH))	CEILIN G	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Sodium hydroxide (Na(OH))	Ceiling	2 mg/m3	US. ACGIH Threshold Limit Values, as amended (2008)
Ammonium hydroxide ((NH4)(OH))	STEL	35 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Ammonium hydroxide ((NH4)(OH))	TWA	25 ppm	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2011)
Ammonium hydroxide ((NH4)(OH))	TWA	25 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
	STEL	35 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
	TWA	25 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	35 ppm	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2011)
Ammonium hydroxide ((NH4)(OH))	STEL	35 ppm	US. ACGIH Threshold Limit Values, as amended (2008)
	TWA	25 ppm	US. ACGIH Threshold Limit Values, as amended (2008)

**Appropriate Engineering Controls**

No data available.

**Individual protection measures, such as personal protective equipment**

**General information:** Provide easy access to water supply and eye wash facilities. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

**Eye/face protection:** Wear safety glasses with side shields (or goggles).

**Skin Protection**

**Hand Protection:** No data available.

**Other:** Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.

**Respiratory Protection:** In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.



**Hygiene measures:** Observe good industrial hygiene practices. Avoid contact with eyes. When using do not smoke. Wash contaminated clothing before reuse. Avoid contact with skin. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace.

**9. Physical and chemical properties**

**Appearance**

**Physical state:** liquid  
**Form:** Spray Aerosol  
**Color:** No data available.  
**Odor:** No data available.  
**Odor threshold:** No data available.  
**pH:** No data available.  
**Melting point/freezing point:** No data available.  
**Initial boiling point and boiling range:** No data available.  
**Flash Point:** Estimated -104.44 °C  
**Evaporation rate:** No data available.  
**Flammability (solid, gas):** No data available.

**Upper/lower limit on flammability or explosive limits**

**Flammability limit - upper (%):** Estimated 9.5 %(V)  
**Flammability limit - lower (%):** Estimated 1.9 %(V)  
**Explosive limit - upper (%):** No data available.  
**Explosive limit - lower (%):** No data available.

**Vapor pressure:** 2,757 - 4,136 hPa (20 °C)  
**Vapor density:** No data available.  
**Density:** No data available.  
**Relative density:** No data available.  
**Solubility(ies)**  
**Solubility in water:** No data available.  
**Solubility (other):** No data available.  
**Partition coefficient (n-octanol/water):** No data available.  
**Auto-ignition temperature:** No data available.  
**Decomposition temperature:** No data available.  
**Viscosity:** No data available.

**10. Stability and reactivity**

**Reactivity:** No data available.  
**Chemical Stability:** Material is stable under normal conditions.  
**Possibility of hazardous reactions:** No data available.  
**Conditions to avoid:** Avoid heat or contamination.  
**Incompatible Materials:** No data available.



**Hazardous Decomposition Products:** No data available.

## 11. Toxicological information

### Information on likely routes of exposure

**Inhalation:** No data available.  
**Skin Contact:** No data available.  
**Eye contact:** No data available.  
**Ingestion:** No data available.

### Symptoms related to the physical, chemical and toxicological characteristics

**Inhalation:** No data available.  
**Skin Contact:** No data available.  
**Eye contact:** No data available.  
**Ingestion:** No data available.

### Information on toxicological effects

#### Acute toxicity (list all possible routes of exposure)

**Oral Product:** ATEmix: 7,591.3 mg/kg  
**Dermal Product:** ATEmix: 4,608.7 mg/kg  
**Inhalation Product:** ATEmix: 47.83 mg/l  
ATEmix : 13.04 mg/l

#### Repeated dose toxicity

**Product:** No data available.

#### Specified substance(s):

Ethanol, 2-butoxy- NOAEL (Rat(Female), Inhalation, 2 yr): < 31 ppm(m) Inhalation  
Experimental result, Key study  
NOAEL (Rat(Female), Oral, 90 d): < 82 mg/kg Oral Experimental result, Key study  
NOAEL (Rabbit(Female, Male), Dermal, 90 d): > 150 mg/kg Dermal  
Experimental result, Key study  
Butane LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation  
Experimental result, Key study  
NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation  
Experimental result, Key study  
Propane NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation  
Experimental result, Key study  
LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation  
Experimental result, Key study

#### Skin Corrosion/Irritation

**Product:** No data available.





**Specified substance(s):**

Ethanol, 2-butoxy- in vivo (Rabbit): Irritating Experimental result, Key study  
Sodium hydroxide estimated Corrosive , 1 min  
(Na(OH)) in vivo (Rabbit): Irritating Experimental result, Weight of Evidence study

**Serious Eye Damage/Eye Irritation**

**Product:** No data available.

**Specified substance(s):**

Ethanol, 2-butoxy- Rabbit, 24 - 72 hrs: Irritating  
Sodium hydroxide Corrosive  
(Na(OH)) Rabbit, 2 d: 10% Sodium Hydroxide- Category 1; 0.5% Sodium Hydroxide- Slightly irritating to eyes

**Respiratory or Skin Sensitization**

**Product:** No data available.

**Specified substance(s):**

Ethanol, 2-butoxy- Skin sensitization:, in vivo (Guinea pig): Non sensitising

**Carcinogenicity**

**Product:** No data available.

**IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:**

No carcinogenic components identified

**US. National Toxicology Program (NTP) Report on Carcinogens:**

No carcinogenic components identified

**ACGIH Carcinogen List:**

No carcinogenic components identified

**Germ Cell Mutagenicity**

**In vitro**

**Product:** No data available.

**In vivo**

**Product:** No data available.

**Reproductive toxicity**

**Product:** No data available.

**Specific Target Organ Toxicity - Single Exposure**

**Product:** No data available.

**Specific Target Organ Toxicity - Repeated Exposure**

**Product:** No data available.

**Aspiration Hazard**

**Product:** No data available.

**Specified substance(s):**

Oils, pine May be fatal if swallowed and enters airways.

**Other effects:** No data available.





## 12. Ecological information

### Ecotoxicity:

#### Acute hazards to the aquatic environment:

##### Fish

<b>Product:</b>	No data available.
<b>Specified substance(s):</b>	
Ethanol, 2-butoxy-	LC 50 (Oncorhynchus mykiss, 96 h): 1,474 mg/l Experimental result, Key study
Butane	LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study
Propane	LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study
Oils, pine	LC 50 (96 h): estimated 5 mg/l
Sodium hydroxide (Na(OH))	LC 50 (Western mosquitofish (Gambusia affinis), 96 h): 125 mg/l Mortality LC 50 (Gambusia affinis, 96 h): < 180 mg/l Experimental result, Supporting study

##### Aquatic Invertebrates

<b>Product:</b>	No data available.
<b>Specified substance(s):</b>	
Ethanol, 2-butoxy-	EC 50 (Daphnia magna, 48 h): 1,550 mg/l Experimental result, Key study
Butane	LC 50 (Daphnia sp., 48 h): 69.43 mg/l QSAR QSAR, Key study
Ammonium hydroxide ((NH <sub>4</sub> )(OH))	EC 50 (48 h): estimated 0.5 mg/l

#### Chronic hazards to the aquatic environment:

##### Fish

<b>Product:</b>	No data available.
<b>Specified substance(s):</b>	
Ethanol, 2-butoxy-	NOAEL (Danio rerio): > 100 mg/l Experimental result, Key study

##### Aquatic Invertebrates

<b>Product:</b>	No data available.
<b>Specified substance(s):</b>	
Ethanol, 2-butoxy-	EC 10 (Daphnia magna): 134 mg/l Experimental result, Key study EC 50 (Daphnia magna): 297 mg/l Experimental result, Key study

##### Toxicity to Aquatic Plants

<b>Product:</b>	No data available.
-----------------	--------------------

#### Persistence and Degradability

##### Biodegradation

<b>Product:</b>	No data available.
<b>Specified substance(s):</b>	
Ethanol, 2-butoxy-	90.4 % Detected in water. Experimental result, Key study



Butane 100 % (385.5 h) Detected in water. Experimental result, Key study  
Propane 100 % (385.5 h) Detected in water. Experimental result, Key study  
50 % (3.19 d) Detected in water. QSAR, Weight of Evidence study  
Ammonium hydroxide 95 % (10 d) The 10-day window requirement is fulfilled.  
(NH<sub>4</sub>)(OH))

**BOD/COD Ratio**

**Product:** No data available.

**Bioaccumulative potential**

**Bioconcentration Factor (BCF)**

**Product:** No data available.

**Partition Coefficient n-octanol / water (log Kow)**

**Product:** No data available.

**Mobility in soil:**

No data available.

**Known or predicted distribution to environmental compartments**

Ethanol, 2-butoxy- No data available.  
Butane No data available.  
Propane No data available.  
Oils, pine No data available.  
Sodium hydroxide (Na(OH)) No data available.  
Ammonium hydroxide ((NH<sub>4</sub>)(OH)) No data available.

**Other adverse effects:** No data available.

**13. Disposal considerations**

**Disposal instructions:** Wash before disposal. Dispose to controlled facilities.

**Contaminated Packaging:** No data available.

**14. Transport information**

**TDG**

UN Number: UN 1950  
UN Proper Shipping Name: Aerosols, flammable  
Transport Hazard Class(es)  
Class: 2.1  
Label(s): -  
EmS No.:  
Packing Group: -  
Environmental Hazards: No  
Marine Pollutant: No  
Special precautions for user: None known.



**IMDG**

UN Number: UN 1950  
UN Proper Shipping Name: Aerosols, flammable  
Transport Hazard Class(es)  
Class: 2.1  
Label(s): –  
EmS No.: F-D, S-U  
Packing Group: –  
Environmental Hazards: No  
Marine Pollutant: No  
Special precautions for user: None known.

**IATA**

UN Number: UN 1950  
Proper Shipping Name: Aerosols, flammable  
Transport Hazard Class(es):  
Class: 2.1  
Label(s): –  
Packing Group: –  
Environmental Hazards: No  
Marine Pollutant: No  
Special precautions for user: None known.

**15. Regulatory information**

**Canada Federal Regulations  
List of Toxic Substances (CEPA, Schedule 1)**

Chemical Identity  
Ethanol, 2-butoxy-

**Export Control List (CEPA 1999, Schedule 3)**  
Not Regulated

**National Pollutant Release Inventory (NPRI)  
Canada. National Pollutant Release Inventory (NPRI) Substances, Part 5, VOCs with Additional Reporting Requirements**

NPRI PT5 Ethanol, 2-butoxy-  
Butane  
Propane

**Canada. National Pollutant Release Inventory (NPRI) (Schedule 1, Parts 1-4)**  
NPRI Ethanol, 2-butoxy-

**Greenhouse Gases**  
Not Regulated

**Controlled Drugs and Substances Act**  
CA CDSI Not Regulated  
CA CDSII Not Regulated  
CA CDSIII Not Regulated  
CA CDSIV Not Regulated  
CA CDSV Not Regulated  
CA CDSVII Not Regulated  
CA CDSVIII Not Regulated



**Precursor Control Regulations**  
Not Regulated

**International regulations**

**Montreal protocol**  
Not applicable

**Stockholm convention**  
Not applicable

**Rotterdam convention**  
Not applicable

**Kyoto protocol**  
Not applicable

**Inventory Status:**

Australia AICS:	On or in compliance with the inventory
Canada DSL Inventory List:	On or in compliance with the inventory
Canada NDSL Inventory:	Not in compliance with the inventory.
Ontario Inventory:	On or in compliance with the inventory
China Inv. Existing Chemical Substances:	On or in compliance with the inventory
Japan (ENCS) List:	Not in compliance with the inventory.
Japan ISHL Listing:	Not in compliance with the inventory.
Japan Pharmacopoeia Listing:	Not in compliance with the inventory.
Korea Existing Chemicals Inv. (KECI):	On or in compliance with the inventory
Mexico INSQ:	On or in compliance with the inventory
New Zealand Inventory of Chemicals:	On or in compliance with the inventory
Philippines PICCS:	On or in compliance with the inventory
Taiwan Chemical Substance Inventory:	On or in compliance with the inventory
US TSCA Inventory:	On or in compliance with the inventory
EINECS, ELINCS or NLP:	Not in compliance with the inventory.

**16. Other information, including date of preparation or last revision**

**Issue Date:** 10/18/2021

**Revision Date:** No data available.

**Version #:** 1.0

**Further Information:** No data available.

**Disclaimer:** This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.